



JUNGLE KING - on flax backing

Artikel Nr. JUKING0085FVPRW

Olive-green leaves of the elephant ear plant on breathable flax fleece.

A touch of the tropics for your walls! This extraordinary surface takes you on a journey into the lush green rainforest. The olive-green leaves of the elephant ear plant radiate freshness and vitality, as if you were standing right by the banks of a clear jungle river. The natural leaf structure adds tangible depth to any space, transforming it into a green oasis.

Order your DIN A5 sample now!

Characteristics


Raw material	Olive-green elephant ear plant leaves
Scent	○ ○ ○
Light fastness	● ● ○
Abrasion resistance	● ● ●
Vibrancy	● ● ○

Technical details


Backing	Flax Backing
Format	Rolled goods, width: 1,360 mm
MOQ	1 m ² (ca. 0.74 running metre)
Weight	240 g/m ²
Thickness	0,5 mm
Flexibility	Bending radii up to 0,5 mm
Translucency	opaque

Material details


Wallpapering technique Do not apply glue to the back of the wallpaper, but to the surface. Please note our glue recommendations.



Overlap and double-cut Each panel overlaps approx. 2 cm with the one next to it. Please note the edge tolerance.



Free match Free match
The naturally scattered materials do not require matching patterns between panels.



Breathable The natural flax fleece backing is breathable, unbleached, ecological and climate regulating.



Processing

Wallpaper

Installation of Organoid® natural surfaces on flax fleece as a wallpaper:

- Wall-pasting technique
- Pay attention to Organoid glue recommendations
- Double cut: Each panel overlaps with the one next to it (approx. 2 cm)
- Cut with scissors, cutter or plotter
- Pre-trials recommended
- In the case of wallpapers, the effect is to be checked after processing three strips. Claims that go beyond the replacement of defective goods will not be accepted.

Processing

Décor

Installation of Organoid® natural surfaces on flax fleece in woodworking (décor):

- Process with normal wood-working machinery
- Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece
- Cover the natural surface with the enclosed separating paper
- pressing temperature. 60°C
- For sensitive wood-working applications, use a counter-balance (enclosed on request)
- Cut with scissors, cutter or plotter
- Pre-trials recommended

Processing

ORGANOID GmbH

6500 Fließ

Nesselgarten 422

www.organoids.com

info@organoids.com

Tel. [+43 5449 200 01](tel:+43544920001)

24.2.2026