

Product	Name	Organoid® HOPS GOLD on golden paper
	Article number	HOPBLI0065GTARW
	Producer	Address ORGANOID GmbH Nesselgarten 422 / Top 5 A-6500 Fließ Austria
Description and applications	Name	Organoid® HOPFEN GOLD on golden paper
	Description	Natural plant Material in medium density on golden paper produced climate neutral in Tyrol
	Applications	As wallpaper As décor, like veneer on backing boards
Plant material and density	Plant material	Hop petals
	Density	Medium, loosely spread, backing material is part of the design
Size and weight	Size	Rolled goods, width 1 360 mm
	Thickness	0.2 mm
	Weight	190 g/m ²
Product requirements	Food-safety	Binding agent safe for usage in contact with food in accordance with EU-regulation 1935/2004
Backing material	Material	Golden paper
	Properties	Shimmering
Technical implementation	Cut	Use scissors, a cutter or a plotter
	Edges	Allow for imperfections 1-2 mm around the edges
	How to install	<u>As wallpaper:</u> <ul style="list-style-type: none"> • Wall-pasting technique: Apply glue directly on the wall, apply wallpaper vertically and press on using a rubber roller • Additional soaking with a sponge and clear, cold water • Double cut: Each panel overlaps with the one next to it (approx. 2 cm) • Free match: The naturally scattered materials do not require matching patterns between panels <u>As décor:</u> <ul style="list-style-type: none"> • Process with normal wood-working machinery • Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs

moisture and glue stains may appear on the front if glue is applied to the fleece

- Cover the natural surface with the enclosed separating paper
- Guidelines:
 - Max. pressing temperature. 60°C
 - Max. pressure 1 kg/cm²
 - Glue application: approx. 100 g/m²
 - Pressing time: approx. 15 minutes

Pre-trials and tests are recommended

Glue recommendations As wallpaper: Glutolin ECC extra clear
As décor, like veneer on backing boards:
White glue

Pay attention to Surface must be clean, dry, weight-bearing, evenly absorbent, smooth, dust-free and neutral in colour. Recently plastered walls must be fully dried. Highly absorbent walls must be prepared with a suitable base.

For sensitive wood-working applications, use a counter-balance (enclosed on request). Symmetrical construction is recommended, which means using the same surface on the front and back side.

Acclimatisation of Organoid natural surfaces:

- Bring product to room temperature before unpacking
- Store product protected from light, at about 20°C and 30-60 % relative humidity.

Storage:

- Rolled goods: hanging system (e.g. paternoster)
- Single panels: horizontal position (e.g. drawer system)

Processing guidelines available at:

www.organoids.com/en/processing