



MOSS GREY - on flax backing, adhesive foil

Artikel Nr. MOSGRA0085FVPRW

Grey moss from upcycling on breathable flax fleece or flax fleece with PVC-free adhesive foil.

A touch of misty forest for your walls! This natural surface transports you to the mystical world of Nordic forests, where silence and wilderness meet. The smoky grey of the moss evokes mist-covered clearings and brings the magical calm of nature straight into your home. The soft texture creates a natural depth that turns any space into a sanctuary – wild, mystical, and unique.

Order your DIN A5 sample now!

Grey moss from upcycling in full, premium coverage, available on Flax fleece and self-adhesive foil – making every application in interior design possible.

Characteristics

Raw material	Upcycled light grey moss
Scent	● ○ ○
Light fastness	● ● ●
Abrasion resistance	● ● ●
Vibrancy	● ○ ○

Technical details


Backing	Flax Backing
Format	Rolled goods, width: 1,360 mm
MOQ	1 m ² (ca. 0.74 running metre)
Weight	600 g/m ²
Thickness	0.8 mm
Flexibility	Bending radii up to 0.5 mm, at least 5 cm flat surface
Translucency	opaque

Material details

Breathable The natural flax fleece backing is breathable, unbleached, ecological and climate regulating.



Free match Free match
The naturally scattered materials do not require matching patterns between panels.



Overlap and double-cut Each panel overlaps approx. 2 cm with the one next to it. Please note the edge tolerance.



Wallpapering technique Do not apply glue to the back of the wallpaper, but to the surface. Please note our glue recommendations.



Processing

Wallpaper

Installation of Organoid® natural surfaces on flax fleece as a wallpaper:

- Wall-pasting technique
- Pay attention to Organoid glue recommendations
- Double cut: Each panel overlaps with the one next to it (approx. 2 cm)
- Cut with scissors, cutter or plotter
- Pre-trials recommended
- In the case of wallpapers, the effect is to be checked after processing three strips. Claims that go beyond the replacement of defective goods will not be accepted.

Processing

Décor

Installation of Organoid® natural surfaces on flax fleece in woodworking (décor):

- Process with normal wood-working machinery
- Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece
- Cover the natural surface with the enclosed separating paper
- pressing temperature. 60°C
- For sensitive wood-working applications, use a counter-balance (enclosed on request)
- Cut with scissors, cutter or plotter
- Pre-trials recommended

Processing

Inspiration



ORGANOID GmbH

6500 Fließ

Nesselgarten 422

www.organoids.com

info@organoids.com

Tel. [+43 5449 200 01](tel:+43544920001)

18.2.2026