



## **SUPERBLOOM - on flax backing**

**Artikel Nr.**

SUPERB0045FVPRW

**Colourful blend of dyed hydrangeas, daisies and more on breathable flax fleece.**

**A true explosion of colour for your walls! Inspired by the natural phenomenon of the superbloom – when entire landscapes burst into a spectacular display of flowers – this surface brings together the vibrant variety of colourful blossoms and petals. Bold, delicate, wild: a tribute to the power of nature that brings pure joy into any space!**

**Order your DIN A5 sample now!**

## Characteristics

|                            |                                                      |
|----------------------------|------------------------------------------------------|
| <b>Raw material</b>        | Colourful blend of dyed hydrangeas, daisies and more |
| <b>Scent</b>               | ○ ○ ○                                                |
| <b>Light fastness</b>      | ● ● ●                                                |
| <b>Abrasion resistance</b> | ● ● ○                                                |
| <b>Vibrancy</b>            | ● ● ○                                                |

## Technical details


|                     |                              |
|---------------------|------------------------------|
| <b>Backing</b>      | Flax Backing                 |
| <b>Format</b>       | Roll, width: 960 mm          |
| <b>MOQ</b>          | 1 lm ( 0.96 m <sup>2</sup> ) |
| <b>Weight</b>       | 210 g/m <sup>2</sup>         |
| <b>Thickness</b>    | 0,2 mm                       |
| <b>Flexibility</b>  | Bending radii up to 0.5 mm   |
| <b>Translucency</b> | light-permeable              |

## Material details


|                   |                                                                                               |
|-------------------|-----------------------------------------------------------------------------------------------|
| <b>Breathable</b> | The natural flax fleece backing is breathable, unbleached, ecological and climate regulating. |
|-------------------|-----------------------------------------------------------------------------------------------|




|                   |                                                                                                  |
|-------------------|--------------------------------------------------------------------------------------------------|
| <b>Free match</b> | Free match<br>The naturally scattered materials do not require matching patterns between panels. |
|-------------------|--------------------------------------------------------------------------------------------------|



|                               |                                                                                           |
|-------------------------------|-------------------------------------------------------------------------------------------|
| <b>Overlap and double-cut</b> | Each panel overlaps approx. 2 cm with the one next to it. Please note the edge tolerance. |
|-------------------------------|-------------------------------------------------------------------------------------------|



|                               |                                                                                                           |
|-------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Wallpapering technique</b> | Do not apply glue to the back of the wallpaper, but to the surface. Please note our glue recommendations. |
|-------------------------------|-----------------------------------------------------------------------------------------------------------|



## Processing

### Wallpaper

Installation of Organoid® natural surfaces on flax fleece as a wallpaper:

- Wall-pasting technique
- Pay attention to Organoid glue recommendations
- Double cut: Each panel overlaps with the one next to it (approx. 2 cm)
- Cut with scissors, cutter or plotter
- Pre-trials recommended
- In the case of wallpapers, the effect is to be checked after processing three strips. Claims that go beyond the replacement of defective goods will not be accepted.

Processing

### Décor

Installation of Organoid® natural surfaces on flax fleece in woodworking (décor):

- Process with normal wood-working machinery
- Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece
- Cover the natural surface with the enclosed separating paper
- pressing temperature. 60°C
- For sensitive wood-working applications, use a counter-balance (enclosed on request)
- Cut with scissors, cutter or plotter
- Pre-trials recommended

Processing

## **ORGANOID GmbH**

6500 Fließ

Nesselgarten 422

[www.organoids.com](http://www.organoids.com)

[info@organoids.com](mailto:info@organoids.com)

Tel. +43 5449 200 01

18.2.2026