



## **WILDSPITZE light - on flax backing**

Artikel Nr. WSP0002020FVPRW

**Hand-scythed Tyrolean Alpine hay in light application thickness on breathable flax fleece.**

**WILDSPITZE light enchants with hand-scythed alpine hay from the Tyrolean Alps – freshly harvested from the mountain meadows surrounding our manufactory in Fliess. The reduced application thickness and translucent flax fleece give this surface a natural lightness and airy appearance. Its subtle fragrance provides a refreshing sense of well-being and noticeably enhances the indoor climate. Bring the Alpine breeze into your home!**

**Order your DIN A5 sample now!**

Regional, hand-cut Alpine hay from the Tyrolean Alps in light coverage on natural non-woven flax backing.

## Characteristics


<b>Raw material</b>	Fragrant Alpine hay
<b>Scent</b>	● ○ ○
<b>Light fastness</b>	● ● ○
<b>Abrasion resistance</b>	● ○ ○
<b>Vibrancy</b>	● ○ ○

## Technical details


<b>Backing</b>	Flax Backing
<b>Format</b>	Rolled goods, width: 1,360 mm
<b>MOQ</b>	1 m <sup>2</sup> ( ca. 0.74 running metre)
<b>Weight</b>	135 g/m <sup>2</sup>
<b>Thickness</b>	0,2 mm
<b>Flexibility</b>	Bending radii up to 0,5 mm
<b>Translucency</b>	light-permeable

## Material details


**Wallpapering technique** Do not apply glue to the back of the wallpaper, but to the surface. Please note our glue recommendations.



**Overlap and double-cut** Each panel overlaps approx. 2 cm with the one next to it. Please note the edge tolerance.



**Free match** Free match  
The naturally scattered materials do not require matching patterns between panels.



**Flame resistant** Firebehaviour classification: B-s1,d0 according to EN ISO 13501-01



**Breathable**

The natural flax fleece backing is breathable, unbleached, ecological and climate regulating.



## Processing

### Wallpaper

Installation of Organoid® natural surfaces on flax fleece as a wallpaper:

- Wall-pasting technique
- Pay attention to Organoid glue recommendations
- Double cut: Each panel overlaps with the one next to it (approx. 2 cm)
- Cut with scissors, cutter or plotter
- Pre-trials recommended
- In the case of wallpapers, the effect is to be checked after processing three strips. Claims that go beyond the replacement of defective goods will not be accepted.

Processing

### Décor

Installation of Organoid® natural surfaces on flax fleece in woodworking (décor):

- Process with normal wood-working machinery
- Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece
- Cover the natural surface with the enclosed separating paper
- pressing temperature. 60°C
- For sensitive wood-working applications, use a counter-balance (enclosed on request)
- Cut with scissors, cutter or plotter
- Pre-trials recommended

Processing

## Inspiration



### ORGANOID GmbH

6500 Fließ

Nesselgarten 422

[www.organoids.com](http://www.organoids.com)

[info@organoids.com](mailto:info@organoids.com)

Tel. [+43 5449 200 01](tel:+43544920001)

18.2.2026