



WILDSPITZE - on flax backing, adhesive foil

Artikel Nr. WSP0000075FVPRW

Hand-scythed Tyrolean Alpine hay in full-surface application on breathable flax fleece or flax fleece with PVC-free adhesive foil.

Say “hay” to pure Alpine charm! WILDSPITZE brings the spirit of the Tyrolean mountains indoors. The hand-scythed alpine hay is harvested from the lush green meadows surrounding our Tyrolean manufactory. This natural surface offers an unmistakable scent and noticeably enhances the indoor climate. Pure nature for the nose and soul.

Order your DIN A5 sample now!

Regional, hand-cut Alpine hay from the Tyrolean Alps in full, premium coverage, available on various backings – making every application in interior design possible.

Characteristics


Raw material	Fragrant Alpine Hay
Scent	○ ○ ○
Light fastness	○ ○ ○
Abrasion resistance	○ ○ ○
Vibrancy	○ ○ ○

Technical details


Backing	Flax Backing
Format	Rolled goods, width: 1,360 mm
MOQ	1 m ² (ca. 0.74 running metre)
Firebehaviour	C-s1, d0 nach EN ISO 13501-01
Weight	790 g/m ²
Thickness	1 mm
Flexibility	Bending radii up to 0.5 mm
Translucency	opaque

Material details


Wallpapering technique Do not apply glue to the back of the wallpaper, but to the surface. Please note our glue recommendations.



Overlap and double-cut Each panel overlaps approx. 2 cm with the one next to it. Please note the edge tolerance.



Free match Free match
The naturally scattered materials do not require matching patterns between panels.



Flame resistant C

Firebehaviour classification: C-s1, d0 according to EN ISO 13501-01



Breathable

The natural flax fleece backing is breathable, unbleached, ecological and climate regulating.



Processing

Wallpaper

Installation of Organoid® natural surfaces on flax fleece as a wallpaper:

- Wall-pasting technique
- Pay attention to Organoid glue recommendations
- Double cut: Each panel overlaps with the one next to it (approx. 2 cm)
- Cut with scissors, cutter or plotter
- Pre-trials recommended
- In the case of wallpapers, the effect is to be checked after processing three strips. Claims that go beyond the replacement of defective goods will not be accepted.

Processing

Décor

Installation of Organoid® natural surfaces on flax fleece in woodworking (décor):

- Process with normal wood-working machinery
- Glue (e.g. white glue) is applied onto the wooden materials, as the fleece absorbs moisture and glue stains may appear on the front if glue is applied to the fleece
- Cover the natural surface with the enclosed separating paper
- pressing temperature. 60°C
- For sensitive wood-working applications, use a counter-balance (enclosed on request)
- Cut with scissors, cutter or plotter
- Pre-trials recommended

Processing

Inspiration



ORGANOID GmbH

6500 Fließ
Nesselgarten 422
www.organoids.com
info@organoids.com
Tel. [+43 5449 200 01](tel:+43544920001)

18.2.2026